

Subject: New equipment

REF NO.61.0XL

STANDARD LONG ROLL TRAILER



Technical specification.

Length: 18.477 to 19.092 mm
(or 60' to 62')
Safety hook 280 mm
Width: 2,540 mm.
Height front: 800 mm.
Height over wheel
Set 750 mm.
Ground clearance: 285 mm.
Tare weight: 9.5 tons
Capacity: 80 or 90 tons

Uses

To transport 20', 30', 40' 45' ISO containers as single or in combinations like 40 + 20 or 45 + 20. Single or double stacked

The units are also very much used for transport of extra wide and long cargo, like tanks, wood, steel etc.



Futher informations:

- Skeletal type frame wiht I beams in steel Rst 52,3 DIN17100
- Rear crossbeam UNP profile diagonally supported
- Box profile above running gear.
- Forklift pockets, reinforced box profiles.
- Support at front for emty stacking.
- Safety coupling at the front
- Reinforced front and coupling mouth.
- Solid reinforced bottom rail.
- Platform constructed of 5 mm steel plate
- Running gear: two rockers arms, box construction.
- Four axles DIN 17100 Rst 52.3
- Eight steel band reinforced solid rubber tires
- Bushings teflon coated (Teflon + steel)
- Bearings make: SKF, Koyo etc.
- Cover over bearing house made by pressed steel
- Lubrication nipples for wheels.
- All screws, nuts and dishes are galvanized.
- Wooden deck, 52 mm Preserved treatment.
- Finish: Completely shot blasted to SSI 55900 SA 2,5. Painting with total layer of 120 microns polyethylene or epoxy painting system.
- Markings: Standard markings, Tara, SWL and customer's logo if provided.
- This piece of equipment can be approved by any classification society like LRS, DNV, GL, ABS etc

For futher information :

NOVATECH ApS
Skudehavnsvej 30
DK-9000 Aalborg

Phone +45 98165009
Fax : +45 98168097
E-mail: sale@novatech.dk
Htp www.novatech.dk