

Ref. No. 60.128

Specification roll trailer 4x15 m / 100 tons .

Capacity: 100 tons equally distributed not self-supporting load.

Length: app 15000 mm + (safety hook 280 mm`)

Width: 4.000 mm

Height: Front: 800 mm
Over wheel set: 830 mm
Ground clearance: 330 mm

Frame: Skeletal type frame I beam in steel DIN 17100 Rst 52.3 with following features: -
Rear crossbeam welded UNP profile diagonally supported.
Box profile above running gear. -
Steel plate above wheels for empty stacking- -
Safety coupling in front. -
Reinforced front and coupling mouth. - solid reinforced bottom rail.
4 pc lifting eyes for moving around of empty trailer, capacity 3 tims tare weight of platform. Placement 2 in front, 2 in rear end.

Platform: Platform construction of 52 mm preserved pinewood rested on cross members
Planks will be screwed on the crossmembers and does not cover the box profile above running gear.

Running gear: 2 rocker arms, box construction
4 axles, DIN 17100 Rst 52.3 140x140 - Ø100 mm
8 Steel band reinforced solid rubber tyres 22"x16"x16". Make: Prodo, Watts
Bushings are Teflon-coated (steel + teflon).
Bearings make: SKF, Koyo or ZWZ
Cover of bearing house made by pressed steel cover,
Lubrication nipple placed in wheel for service



- Additional. 2+2 D-rings lashings 36 tons,
Lashing rail along side beams
8x2 stanchion pockets 70x130 mm on side beams.
2x2 stanchion pockets 70x130 mm on end beams
- All screws, nuts and dishes are galvanized.
- Finish: Trailer complete shot blasted to SSI 55900 AS 2,5 after welding
Painting 1 full coat Zinc, 1 full top coat. Total thickness 120 micron.
- Marking Costume logo on 2 side of trailer provided SWL 100 tons Tare weight on 2 sides.
- Certification The trailers can be approved by any classification like LRS, DNV, TUV etc. if ordered and paid by client..

NOVATECH