



Ref.no. 60.202

### **Specification for cassette SWL 90 t (VER.C)**

- Capacity:** 90 tons equally distributed not self-supporting load  
(80 t for 2x20' container load).
- Length:** 13800 mm.
- Width:** 2800 mm.
- Height:** 880 mm. (on 20 mm rubber feet)
- Tare:**
- Frame:** Skeletal type frame, 2 longitudinal UPE beams in steel DIN 17100 Rst 52.3  
Cross members as IPE 140.  
2 forklift places  
4 stacking pins for empty stacking.  
4 lashing points.  
Flat guide bars 10x100- 3 pcs all over the length.
- Platform:** Platform constructed of 27 mm water resistant plywood, rested on cross members and fixed by self tapping screws (galvanized).
- Optionally:** Lashing rail along side beams.  
ISO openings for 20', 30', 40' and 45' containers position and swap body type (14 pc in total).
- Finish:** Cassette completely shot blasted to SSI 55900 Sa 2,5 after welding  
Painting: 1 full primer, 1 full top coat. Total thickness 120 micron.  
Colour: RAL
- Marking:** SWL 90 tons and Tare weight on front and 2 sides.  
Fleet number - front/rear and both sides.
- Certification:** The cassette can be approved by any classification: LRS, DNV, TUV etc. If ordered and paid for by the client.